



# STYLE BETON

## Deco Create – Stamped Wall

<b>DESCRIPTION</b>	The Deco Create , ready to use product, dry, hydrophobic fillers, available in various colors for coating internal and external walls. It can be applied directly to concrete, brick or dry wall and then imprinted with special molds to make a perfect imitation of stone, bricks, pebbles, etc. The final phase is colored with water-soluble Decochrom or Decochrom Neutral, which protects the surface.
<b>Color</b>	Available in 3 colors. At the request may be produced in other colors.
<b>Restrictions</b>	Do not apply the product of the likelihood of rain. The temperature must not be below 8 ° C and above 28 ° Celsius.
<b>Packaging</b>	25 kg
<b>Storage</b>	At room temperature onto pallets. Protect from moisture.
<b>Application</b>	<p>The Deco Create is advised to be applied to clean surfaces, free of dust, oil and other substances. The surfaces should not be hydrophobic. It can be applied directly to concrete, bricks, plasterboard, cement and existing plaster, where the plaster does not require dismantling. Before the application is good surfaces to be moistened. The product is a powder which should be mixed with water 20% by mechanical mixing to ensure the optimum mix. In cases where the mixing is by hand, be sure the mixture is homogeneous, before the application.</p> <p>The mixture should be applied within one hour of preparation and having rested for 5-10 minutes to allow for better dissolution of the additives in the formulation.</p> <p>Before we begin the process of stamping, a 2 mm layer of plaster Deco Create should be applied before the main application layer. The ready plaster is applied with a spatula or</p>

	<p>by machine with a minimum thickness of 10mm and maximum 45mm. After grinding the main layer, we wait for 10 min and we start stamping, using the Style Liquid Release and special stamps for wall Style Beton. The next day the special Deco Create plaster is still pliable and have the opportunity with specific tools to make corrections in the joints. After two days the special soluble color Decochrom and give the final appearance of stone, brick etc.</p>
<p><b>CLEANING</b></p>	<p>The tools are recommended to be cleaned immediately after use with water.</p>
<p><b>HEALTH AND SAFETY</b></p>	<p>Read the label before use. During the preparation of surfaces avoid the inhalation of dust. Use a face mask and gloves. It does not contain toxic.</p>
<p><b>GENERAL INFORMATION</b></p>	<p>. Note that the technical application and the experience of work teams will affect the final aesthetic result of the floor.</p> <p>The information and in particular the recommendations relating to the application and final use of products «STYLE BETON» given in good faith, based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual application conditions are such that no guarantee can be given in respect of merchantability or fitness for a particular purpose and no liability of any legal relationship can be established against the company based here in labeling information, written recommendations, or other advice offered. Respect the rights of others is essential. Users must always refer to the most recent version of this.</p> <div data-bbox="858 1473 1023 1653" data-label="Image"> </div> <p style="text-align: center;"><b>STYLE BETON</b></p> <p style="text-align: center;"><b>Terma Aisopou, Kalochori, Thessaloniki, Greece, 54628</b>  <b>TEL. : 0030 2310 - 920831, FAX : 0030 2310 - 920832,</b>  <a href="http://www.stylebeton.com">www.stylebeton.com</a> , <a href="mailto:info@stylebeton.com">info@stylebeton.com</a></p>